



3812 SERIES

Surface Mount

3812 Series directional LEDs feature 20 high intensity LEDs with individual reflectors to provide truly outstanding light output in a very cost-effective package. Featuring fifteen flash patterns and synchronisation capability, offering fit-and-forget maintenance-free operation and low amp draw.

Models


PART NO.	VOLTAGE	AMPS	MOUNT
3812X	12-48	0.4	Surface

Replace X in part number with desired color: A=amber, B=blue, C=clear, R=red

Features and Benefits

- Tough, clear polycarbonate housing with encapsulated electronics
- Fifteen flash patterns (seven with phase 1 & 2 + steady burn)
- Synchronisable with additional units
- Discrete units are colourless when not illuminated
- ECE R65 (Amber & Blue)
- ECE R10-05 (EMC)
- Temperature Range: -30°C to +50°C
- 3 Years Warranty

Dimensions



FLASH PATTERNS

- | | | |
|----|--------------------------------|---------|
| 1 | ECE R65 DOUBLE FLASH (DEFAULT) | |
| 2 | ECE R65 DOUBLE FLASH | PHASE 2 |
| 3 | ECE R65 SINGLE FLASH | PHASE 1 |
| 4 | ECE R65 SINGLE FLASH | PHASE 2 |
| 5 | ECE R65 QUAD FLASH | PHASE 1 |
| 6 | ECE R65 QUAD FLASH | PHASE 2 |
| 7 | STEADY BURN | |
| 8 | TRIPLE FLASH (75FPM) | PHASE 1 |
| 9 | TRIPLE FLASH (75FPM) | PHASE 2 |
| 10 | SINGLE FLASH (75FPM) | PHASE 1 |
| 11 | SINGLE FLASH (75FPM) | PHASE 2 |
| 12 | DOUBLE FLASH (75FPM) | PHASE 1 |
| 13 | DOUBLE FLASH (75FPM) | PHASE 2 |
| 14 | QUAD FLASH (75FPM) | PHASE 1 |
| 15 | QUAD FLASH (75FPM) | PHASE 2 |
| 16 | OFF | |